

Travel
Industry
Products

GENICOM ATB1600, 1800, 2000 Printers



A family of ATB printers presenting innovative solutions for travel document printing requirements.

The Reliability Standard for Travel

Document Printing.

- Outstanding reliability in an advanced, high-volume ATB printer.
- Long printing life and reduced maintenance.
- Exceptional pre-sale and after-sale support.

Your Choice of Print Technologies.

- *ATB1600*
 - Direct thermal
 - 203 x 203 dpi
 - No consumables
- *ATB1800*
 - Direct thermal or thermal transfer
 - 203 x 203 dpi
 - User-selectable print mode
 - Choice of single-pass or multipass ribbons
- *ATB2000*
 - Xerographic print technology
 - 240 x 240 dpi
 - Superior laser quality print
 - Very cost-effective for high-volume printing

All the Best Features.

- Prints up to 40 coupons per minute.
- 3 secure high-capacity coupon input bins (1000-coupon capacity).
- Easy-access 125-coupon output bin (optional secure 1000-coupon output bin).
- Secure coupon reject bin (50-coupon capacity).
- Supports the full IATA ATB2 magnetics requirements.

Typical Applications

- Medium- to high-volume print environments for airports, travel agencies, cruise lines, rails, etc.
- Pocket itineraries, rental car agreements, maps, custom logos, special promotional coupons, and vouchers

GENICOM
Shared Multifaceted Solutions

GENICOM ATB1600, 1800, 2000 Printers

Travel
Industry
Products

Printing

Print Engine:

- ATB1600: Direct thermal
- ATB1800: Direct thermal or thermal transfer
- ATB2000: Xerographic

Resolution:

- ATB1600 and 1800: 203 x 203 dpi
- ATB2000: 240 x 240 dpi

Print Speed: Up to 40 coupons per minute, while writing and verifying magnetics

Standard Fonts: OCR-A

- Gothic (10 point, 10 cpi, normal)
- Gothic (10 point, 17 cpi, normal)
- Gothic (10 point, 17 cpi, bold)
- Gothic (12 point, 10 cpi, bold)

Line Spacing: 6 lpi

Document Handling

- ATB1600: Direct thermal paper vertical Z-fold stock
- ATB1800: Direct thermal or plain paper vertical Z-fold stock
- ATB2000: Plain paper vertical Z-fold stock

Consumables

- ATB1600: User-replaceable print head*
- ATB1800: User-replaceable print head*, single-pass or multipass ribbon
- ATB2000: Developer kit, OPC kit, Fuser kit

*No tools required

Software

- AEA/PECTAB down-line loadable application software

Interfaces and Connectivity

- RS-232C serial port

Physical

Standard Size (HxWxD):

- 28.63 x 13.75 x 28.38 inches
(72.72 x 34.93 x 72.09 cm)

Rack Mount Size (HxWxD):

- 26.00 x 13.75 x 28.38 inches
(66.04 x 34.93 x 72.09 cm)

Printer Weight:

- ATB1600: 140 lbs (63.50 kg)
- ATB1800: 145 lbs (65.77 kg)
- ATB2000: 150 lbs (68.04 kg)

Acoustics:

- Printing: 55 dBA
- Idle: 40 dBA

Operating Environment

- Low Voltage:** 95 to 135 VAC, 47 to 83 Hz
- High Voltage:** 190 to 265 VAC, 47 to 63 Hz
- Operating Temperature:** 40° to 104° F (5° to 40° C)
- Operating Humidity:** 20% to 85% (relative)
- Operating Altitude:** -1000 to 8200 feet (-305 to 2500 m)

Regulatory Agency Approvals

- FCC Part 15 Level A – Verified
- UL 1950 – Listed
- UL-CNL 950 – Listed
- Radio Interference Regulation CRC c. 1374 Class A – Verified
- EN60950/IEC 950 – Certified
- VDE0878, A – Verified
- Factory ISO 9002 Registered
- UL and BSI

Options

- 3.5-inch floppy drive
- 1000-coupon internal stacker
- Choice of 256K or 1MB of nonvolatile memory for additional image and font storage
- Multifunction board to support a parallel port, second serial port, and/or floppy disk drive controller
- Internal modem



Internal View

GENICOM is a registered trademark of GENICOM Corporation. All other company and product names are trademarks or registered trademarks of their respective owners. Specifications are subject to change without notice. Copyright © 1997 GENICOM

For more information, contact GENICOM at:

United States	1-800-GENICOM	Germany	49-6196-65990
Australia	61-2-9417-6411	Italy	39-2-253041
Belgium	32-2-712-6270	Singapore	65-28-64240
Canada	800-268-0464	Spain	34-1-351-48-99
Denmark	45-42-421120	Sweden	46-31-876-500
France	33-1-69-542-317	United Kingdom	44-1252-744400

Contact us on the internet: www.genicom.com (U.S.)
www.genicom.ca (Canada)
info@genicom-intl.com (International)

GENICOM
Shared Multifaceted Solutions

4501 S. General Bruce Drive
Suite 50
Temple, TX, U.S.A.
76502